



# Trimble R750

## GNSS RECEIVER

### KEY FEATURES

- ▶ Trimble® Maxwell™ 7 GNSS ASIC with 672 channels
- ▶ Advanced satellite tracking with Trimble 360 receiver technology
- ▶ Trimble ProPoint™ GNSS positioning engine. Engineered for improved accuracy and productivity in challenging GNSS conditions
- ▶ Convenient front panel display and configuration
- ▶ Wi-Fi and 4G LTE connectivity
- ▶ Bluetooth®, Ethernet, serial and USB support
- ▶ 8 GB internal memory
- ▶ Data logging internally and to external drive
- ▶ USB-C PD charging
- ▶ Support for RTK level precision Trimble CenterPoint® RTX corrections technology
- ▶ Trimble xFill® correction outage technology

Learn more:  
[geospatial.trimble.com/trimble-r750](https://geospatial.trimble.com/trimble-r750)



**PERFORMANCE SPECIFICATIONS**

**GNSS MEASUREMENTS**

Advanced Trimble Maxwell 7 Custom GNSS Chips with 672 channels  
 Trimble EVEREST™ Plus multipath signal rejection  
 Constellation agnostic, flexible signal tracking and improved positioning<sup>1</sup> in challenging GNSS environments with Trimble ProPoint GNSS technology  
 High-precision multiple correlator for GNSS pseudorange measurements  
 Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low time domain correlation, and high-dynamic response  
 Very low noise carrier phase measurements with <1 mm precision in a 1 Hz bandwidth  
 MSS Band (2-channels): Trimble CenterPoint RTX correction service and OmniSTAR® by subscription  
 Reduced downtime due to loss of radio signal or cellular connectivity with Trimble xFill technology  
 Signals tracked simultaneously

- GPS: L1C/A, L1C, L2C, L2E, L5
- GLONASS: L1C/A, L1P, L2C/A, L2P, L3
- SBAS (WAAS, EGNOS, GAGAN, MSAS): L1C/A, L5
- Galileo: E1, E5A, E5B, E5 AltBOC, E6<sup>2</sup>
- BeiDou: B1, B1C, B2, B2A, B2B, B3
- QZSS: L1C/A, L1S, L1C, L2C, L5, L6
- NavIC (IRNSS): L5
- L-band: CenterPoint RTX

Positioning rates: 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz, 50 Hz

**POSITIONING PERFORMANCE<sup>3</sup>**

**STATIC GNSS SURVEYING**

**High-Precision Static**

Horizontal	3 mm + 0.1 ppm RMS
Vertical	3.5 mm + 0.4 ppm RMS

**Static and Fast Static**

Horizontal	3 mm + 0.5 ppm RMS
Vertical	5 mm + 0.5 ppm RMS

**REAL TIME KINEMATIC SURVEYING**

**Single Baseline <30 km**

Horizontal	8 mm + 1 ppm RMS
Vertical	15 mm + 1 ppm RMS

**Network RTK<sup>4</sup>**

Horizontal	8 mm + 0.5 ppm RMS
Vertical	15 mm + 0.5 ppm RMS

**RTK start-up time for specified precisions<sup>5</sup>**

2 to 8 seconds

**TRIMBLE RTX CORRECTION SERVICES**

**CenterPoint RTX<sup>6</sup>**

Horizontal	2 cm (0.06 ft) RMS
Vertical	5 cm (0.16 ft) RMS
RTX convergence time for specified precisions in Trimble RTX Fast regions	< 1 min
RTX convergence time for specified precisions in non RTX Fast regions	< 3 min

**TRIMBLE xFILL<sup>7</sup>**

Horizontal	RTK <sup>8</sup> + 10 mm (0.03 ft)/min RMS
Vertical	RTK <sup>8</sup> + 20 mm (0.06 ft)/min RMS

**TRIMBLE xFILL PREMIUM<sup>7</sup>**

Horizontal	3 cm RMS
Vertical	7 cm RMS

**CODE DIFFERENTIAL GNSS POSITIONING**

Horizontal	0.25 m + 1 ppm RMS
Vertical	0.50 m + 1 ppm RMS
SBAS <sup>9</sup>	typically <5 m 3DRMS

# Trimble R750 GNSS RECEIVER

## HARDWARE

### PHYSICAL

Keyboard and display		
	Display 32 characters by 4 rows	
	On/Off key for one-button startup	
	Escape and Enter keys for menu navigation	
	4 arrow keys (up, down, left, right) for option scrolls and data entry	
Dimensions (L x W x D)	269 mm (10.6 in) x 141 mm (5.5 in) x 61 mm (2.4 in)	
Weight	2.05 kg (4.52 lb)	
Temperature <sup>10</sup>		
	Operating	-40 °C to +65 °C (-40 °F to +149 °F)
	Storage	-40 °C to +80 °C (-40 °F to +176 °F)
Humidity	93% humidity at 40 °C for a duration of 3 hours (IEC-60945 Method 8.3)	
Ingress Protection	IP67 for temporary submersion to depth of 1 m (3.3 ft), dustproof	
Shock and vibration		
	Pole drop	Designed to survive a 1.1 m (3.6 ft) pole drop onto a hard surface
	Shock - Non-operating	To 75 g, 6 ms
	Shock - Operating	To 40 g, 10 ms, saw-tooth
		IEC 60945 Method 8.7
	Vibration	Random 6.2 g RMS operating
		9.8 g RMS 24-2000 Hz for 1 hrs each axis survival

### ELECTRICAL

Internal		
	Integrated internal battery 7.26 V, 6700 mAh, Lithium-ion	
	Internal battery operates as a UPS during an ext power source failure	
	Internal battery will charge from external power source as long as source can support the power drain and is more than 12.5 VDC	
	Integrated charging circuitry	
External		
	Power input on 7-pin 0-shell Lemo connector is optimized for lead acid batteries with a cut-off threshold of 11.5 V, Maximum 28 VDC	
	Power input on the 26-pin D-sub connector has a cut-off threshold of 10.5 V	
	Power source supply (Internal/External) is hot-swap capable in the event of power source removal or cut off	
	DC external power input with over-voltage protection	
	Receiver automatically turns on when connected to external power	
Power consumption	6.6 W in rover mode with internal receive radio	
	8.5 W in base mode with internal transmit radio	
Operation time on internal battery		
Rover	7 hours 450 MHz UHF or cellular receive (Internal or Controller via Bluetooth)	
Base station		
	4.8 hours 2.0 W 450 MHz UHF transmit	
	5.5 hours 0.5 W 450 MHz UHF transmit	

### CERTIFICATIONS<sup>11</sup>

Safety	IEC 62368-1, IEC 60950-1, IEC 62311, IEEE C95.3, UN 38.3, UL 2054
FCC	Part 15 Subpart B (Class B device), subpart C Section 15.2.47, Part 90, Part 22/24/27, part 2, KDB 447498 D01
Canada	ICES-003 (Class B). RSS-GEN, RS-102, RSS-247, RSS-130/132/133/139/199.
EU	RED 2014/53/EU, EN 300 113, EN 300 328, EN 301 908, EN 303 413, EN IEC 62368-1, RoHS Directive 2011/65/EU, WEEE Directive 2012/19/EU.
UKCA	S.I. 2017 No. 1206, S.I. 2016 No. 1091, S.I. 2016 No. 1101.
ACMA	AS/NZS 4268, AS/NZS CISPR 32
Communications	PTCRB, Bluetooth SIG

## COMMUNICATIONS AND DATA STORAGE

Serial 1 (COM1)	7-pin 0S Lemo, Serial 1, 3-wire RS-232	
Serial 2 (COM2)	26-pin D-sub, Serial 2, 5-wire RS232, using adaptor cable (Selectable)	
	26-pin D-sub, Serial 2, 4-wire RS422, using adaptor cable (Selectable)	
Serial 3 (COM3)	26-pin D-sub, Serial 3, 3-wire RS232, using adaptor cable (Selectable)	
Serial 4 (COM4)	26-pin D-sub, Serial 4, 4-wire RS422, using adaptor cable (Selectable)	
1PPS (1 Pulse-per-second)	Supported on both Lemo and 26-pin D-sub	
Event In	Supported on Lemo	
USB	USB v2.0 (Supports USB-PD charging)	
Ethernet	Through a multi-port adaptor	
Wi-Fi	Fully-integrated, fully-sealed 2.4/5 GHz Wi-Fi module	Simultaneous Access Point (AP) and Client modes
Bluetooth wireless technology	Fully-integrated, fully-sealed 2.4 GHz Bluetooth module <sup>6</sup>	
Cellular <sup>12</sup>	Fully-integrated, fully-sealed LTE compliant module	Bands 1:2:3:4:5:7:8:12:18:19:20:28

## NETWORK PROTOCOLS

HTTP (web browser GUI)	HTTP, HTTPS	
NTP Server	Yes	
TCP/IP or UDP	Yes	
NTRIP	NTRIP v1 and v2, Client Server and Caster modes	
mDNS/uPnP Service discovery	Yes	
Dynamic DNS	Yes	
eMail alerts	Yes	

## INTEGRATED UHF RADIO

450 MHz	Fully-integrated, internal 403–473 MHz, 12.5 kHz or 25 kHz spacing configurable by Trimble	
Channel spacing (450 MHz)	–114 dBm (12 dB SINAD)	
Transmit Power (450 MHz)	0.5 W, 2.0 W (2.0 W available only in certain countries)	

## CELLULAR SUPPORT

Internet-based correction streams: (IBSS, VRS, NTRIP)	Internal LTE modem Connected smartphone Connected Trimble Controller [Trimble Access™]	
Remote access	Using DynDNS and appropriate service	

## SUPPORTED DATA FORMATS

Correction inputs	CMRx, CMR+, CMR, RTCM 2.x, RTCM 3	
Correction outputs	RTCM 2.x, CMR, CMR+, CMRx, RTCM 3	
Data outputs	NMEA 0183, GSOFF, 1PPS Time Tags	

- Challenging GNSS environments are locations where the receiver has sufficient satellite availability to achieve minimum accuracy requirements, but where the signal may be partly obstructed by and/or reflected off of trees, buildings, and other objects. Actual results may vary based on user's geographic location and atmospheric activity.
- The current capability in the receivers is based on publicly available information. As such, Trimble cannot guarantee that these receivers will be fully compatible with a future generation of Galileo satellites or signals.
- Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMI and multipath clean environment, optimal GNSS constellation configurations, along with the use of survey practices that are generally accepted for performing the highest-order surveys for the applicable application including occupation times appropriate for baseline length. Baselines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.
- Networked RTK PPM values are referenced to the closest physical base station
- May be affected by atmospheric conditions, signal multipath, obstructions and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
- RMS performance based on repeatable in field measurements. Achievable accuracy and initialization time may vary based on type and capability of receiver and antenna, user's geographic location and atmospheric activity, scintillation levels, GNSS constellation health and availability and level of multipath including obstructions such as large trees and buildings. Average initialization times when using GPS, GLONASS, Galileo, and BeiDou.
- Accuracies are dependent on GNSS satellite availability. xFill positioning without an xFill Premium subscription ends after 5 minutes of radio downtime. xFill Premium will continue beyond 5 minutes providing the solution has converged, with typical precisions not exceeding 3 cm horizontal, 7 cm vertical. xFill is not available in all regions, check with your local sales representative for more information.
- RTK refers to the last reported precision before the correction source was lost and xFill started.
- Depends on SBAS system performance.
- Operating up to +65 °C ambient when the device is powered by external DC supply and the battery is fully charged or is not being charged.
- Operating up to +30 °C ambient when the battery is being charged by an external DC supply
- Operating up to +48 °C ambient when the device is powered by a USB-PD battery or charger.
- More certification is available upon request.
- Verizon is not a supported network in USA.

Specifications subject to change without notice.



Contact your local Trimble Authorized Distribution Partner for more information

**NORTH AMERICA**  
Trimble Inc.  
10368 Westmoor Dr  
Westminster CO 80021  
USA

**EUROPE**  
Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

**ASIA-PACIFIC**  
Trimble Navigation  
Singapore PTE Limited  
3 HarbourFront Place  
#13-02 HarbourFront Tower Two  
Singapore 099254  
SINGAPORE

